

LED line PRIME

Code: 204522-DALI

EAN: 5905378220034

Panel Backlit 34W 4000K 4760lm
UGR<19 62x62 DALI PRIME



The PRIME Backlit LED line panel with 34W and 4000K color temperature is an ideal solution for demanding applications. By generating a luminous flux of 4,760 lumens, it provides efficient and energy-efficient lighting, achieving a capacity of 140 lm/W. Thanks to the low brightness index UGR<19 and the high quality of aluminum and polystyrene, this product is distinguished by durability and comfort of use.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	C
Warranty	5
Power	• 34 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	02
IEC protection class	II
Luminous efficacy	140
Luminous flux	4760
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
Survival factor	0.9

Parameter	Value
Dimmable function	Triac
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	90
LED type	SMD LED 2835
LED quantity	64
Power Factor	0,9
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Colour	White
Material (housing)	Aluminium
Material (cover)	Polystyrene

LED line PRIME

Code: 204522-DALI

EAN: 5905378220034

**Panel Backlit 34W 4000K 4760lm
UGR<19 62x62 DALI PRIME**


Technical drawing

Light distribution


Additional product photos




Logistics data



Single packaging



Bulk packaging



Europallet

LED line PRIME

Code: 204522-DALI

EAN: 5905378220034

**Panel Backlit 34W 4000K 4760lm
UGR<19 62x62 DALI PRIME**

Example application