

LED line PRIME

Code: 204522-DALI

EAN: 5905378220034

Backlit Panel 4000K 34W 4760lm IP20
62x62cm white UGR<19 PRIME DALI



The PRIME Backlit LED line panel with 34W and 4000K color temperature is an ideal solution for demanding applications. By generating a luminous flux of 4,760 lumens, it provides efficient and energy-efficient lighting, achieving a capacity of 140 lm/W. Thanks to the low brightness index UGR<19 and the high quality of aluminum and polystyrene, this product is distinguished by durability and comfort of use.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	C
Warranty	5
Power	• 34 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	02
IEC protection class	II
Luminous efficacy	140
Luminous flux	4760
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
Survival factor	0.9
Dimmable function	Dali

Parameter	Value
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	90
LED type	SMD LED 2835
LED quantity	64
Power Factor	0,9
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	30 mm
Colour	White
Material (housing)	Aluminium
Material (cover)	Polystyrene
DALI	• YES

LED line PRIME

Code: 204522-DALI

EAN: 5905378220034

Backlit Panel 4000K 34W 4760lm IP20
62x62cm white UGR<19 PRIME DALI


Technical drawing

Light distribution

Additional product photos




Logistics data




Single packaging

Quantity	1
Width	35 mm
Height	640 mm
Length	630 mm
Weight	1,9 kg



Bulk packaging

Quantity	5
Width	200 mm
Height	655 mm
Length	645 mm
Volume	0,085 m3
Weight	12,5 kg
Comments	



Europallet

Height	1320 mm
Quantity in layer	30
Number of layers	2
Bulk quantity	60
Weight	150 kg

LED line PRIME

Code: 204522-DALI

EAN: 5905378220034

**Backlit Panel 4000K 34W 4760lm IP20
62x62cm white UGR<19 PRIME DALI**

Example application