

LED line LITE

Code: 200814

EAN: 5905378200814

**DOWNLIGHT MOLLY 3000K 24W 2350lm
round IP20 White LITE**



LED line LITE Downlight MOLLY with 24W power and 2350 lm light stream is a solution that combines modern design with high energy efficiency. The colour temperature of 3000K provides warm, pleasant light, and the Ra>80 colour rendering rate guarantees the naturalness of the shades. IP20 and IK05 leak class provide adequate protection under different indoor conditions.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	3
Power	• 24 W
Voltage	• 170-260 V AC
Correlated colour temperature	• 3000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IEC protection class	II
Luminous efficacy	100
Luminous flux	2350
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9

Parameter	Value
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	110
LED type	SMD LED 2835
LED quantity	120
Power Factor	0,5
Number of on/off cycles	20000
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Mounting hole diameter	190-210
Height	26
Fixture's diameter	220 mm
Colour	White
Material (housing)	Polycarbonate


LED line LITE

Code: 200814


EAN: 5905378200814

**DOWNLIGHT MOLLY 3000K 24W 2350lm
round IP20 White LITE**

Technical drawing






Light distribution



Additional product photos



Logistics data



Single packaging

Quantity	1
Width	250 mm
Height	36 mm
Length	230 mm
Weight	0,284 kg

Bulk packaging

Quantity	40
Width	390 mm
Height	472 mm
Length	472 mm
Volume	
Weight	12 kg

Europallet

Quantity	640
Height	1,9 m
Quantity in layer	160
Number of layers	4
Bulk quantity	16
Weight	222 kg

LED line LITE

Code: 200814

EAN: 5905378200814

**DOWNLIGHT MOLLY 3000K 24W 2350lm
round IP20 White LITE**

Example application

