

LED line PRIME Code: 204522-AW3HAT EAN: 5905378216648

## Panel Backlit 34W 4000K 4760lm UGR<19 62x62 emergency module 3h autotest PRIME



Backlit panel 34W 4000K from LED line PRIME is a modern light source with high light performance of 4760 lm. It is characterized by a low brightness index of UGR<19, which provides comfortable lighting conditions. Made of aluminium and polystyrene, the panel has a durability of L70B50 of as much as 50,000 hours. The built-in emergency module runs for three hours in case of power failure.





#### **Technical data**

Parameter	Value
Operating time in emergency mode	3 h
Emergency module test	autotest
Voltage	• 220-240 V AC
Luminous efficacy	140
Colour of the light	White
Energy efficiency class 2019/2015	С
Luminous flux	4760
Colour consistency in McAdam ellipses	≤6
Warranty (years)	5
IP protection rating	IP20
Dimmable function	Triac
Survival factor	0.9
Lifetime L70B50	50 000 h
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	White

Parameter	Value
The lumen maintenance factor	96
Beam angle	90
Material (cover)	polystyrene
Material (housing)	Aluminium
LED type	SMD LED 2835
LED quantity	64
Power Factor	0,9
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
IEC protection class	II
IK protection rating	02
Lamp's warm-up time to 60%	ls
Correlated colour temperature	• 4000 K
Power	• 34 W



LED line PRIME Code: 204522-AW3HAT EAN: 5905378216648

# Panel Backlit 34W 4000K 4760lm UGR<19 62x62 emergency module 3h autotest PRIME

Technical drawing


Light distribution


#### Additional product photos






#### Logistics data







Single packaging

**Bulk packaging** 

Europallet

### MORE EFFICIENCY FOR THE LED WORLD



LED line PRIME Code: 204522-AW3HAT EAN: 5905378216648

Panel Backlit 34W 4000K 4760lm UGR<19 62x62 emergency module 3h autotest PRIME

**Example application**