

LED line LITE Code: 203310 EAN: 5905378203310

LED line LITE Floodlight LUMINO 50W 4000K 5000lm





LUMINO 50W LED line LITE is an innovative solution with high light performance of 5,000 lumens at 50 W. Thanks to the colour of the light 4000 K offers natural, white lighting. The product is characterized by IP65 protection class, which provides resistance to dust and water, and IK05 protection level, guaranteeing durability and impact resistance.















Technical data

Parameter	Value
Energy efficiency class 2019/2015	F
Warranty	3
Power	• 50 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	70
IK protection rating	05
IEC protection class	1
Luminous efficacy	100
Luminous flux	5000
The lumen maintenance factor	96
Lifetime L70B50	25 000 h


Parameter	Value
Survival factor	0.9
Colour consistency in McAdam ellipses	≤ 6
Frequency of the supply voltage	50/60Hz
Beam angle	110
LED type	SMD LED
LED quantity	56
Power Factor	0,9
Lamp's warm-up time to 60%	ls
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Material (housing)	Die cast aluminium
Material (cover)	tempered glass



LED line LITE Code: 203310 EAN: 5905378203310


LED line LITE Floodlight LUMINO 50W 4000K 5000lm

Technical drawing



Light distribution

Luminous [cd/klm]





Additional product photos






Logistics data







Single packaging Bulk packaging Europallet

MORE EFFICIENCY FOR THE LED WORLD



LED line LITE Code: 203310 EAN: 5905378203310

LED line LITE Floodlight LUMINO 50W 4000K 5000lm

Example application