

LED line LITE



Code: 203952

EAN: 5905378203952

**Backlit Panel 2in1 4000K 40W 4000lm
IP20 30x120cm black Surface-
mounted/Recessed LITE**



The Backlit Panel 2in1 40W 4000K 4000LM is a high-quality lighting fixture from the LED line LITE brand, designed for modern spaces. With a power of 40 W and a luminous efficiency of 100 lm/W, the panel generates a luminous flux of 4000 lumens. It features a light color of 4000 K, providing neutral lighting. The housing made of metal and polystyrene ensures durability, while the design allows for various mounting methods.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	3
Power	• 40 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	02
IEC protection class	I
Luminous efficacy	100
Luminous flux	4000
The lumen maintenance factor	96
Lifetime L70B50	30 000 h

Parameter	Value
Survival factor	0.9
Dimmable function	-
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	120
Power Factor	≥0,95
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Mounting hole diameter	60-260 x 600 [mm]
Height	38 mm
Material (housing)	Metal
Material (cover)	Polystyrene


LED line LITE

Code: 203952

EAN: 5905378203952

**Backlit Panel 2in1 4000K 40W 4000lm
IP20 30x120cm black Surface-
mounted/Recessed LITE**

Technical drawing






Light distribution

Additional product photos



Logistics data



Single packaging

Width	1205 mm
Height	45 mm
Length	305 mm
Weight	1,78 kg

Bulk packaging

Quantity	4
Width	325 mm
Height	200 mm
Length	1225 mm
Volume	0,079 m3
Weight	7,5 kg

Europallet

Quantity	48
Height	1,4 m
Quantity in layer	
Number of layers	
Bulk quantity	12
Weight	120 kg

LED line LITE

Code: 203952

EAN: 5905378203952

**Backlit Panel 2in1 4000K 40W 4000lm
IP20 30x120cm black Surface-
mounted/Recessed LITE**

Example application