

LED line PRIME

Code: LL-200-12-ALU

EAN: 5905378217973

**Power Supply 200-12 IP67 200W 12V  
Aluminum PRIME**

**New**

LED line PRIME LL-200-12-ALU is a reliable power source with a maximum power of 200 W, with an output voltage of 12 V. It ensures high efficiency at  $\geq 0.91$  and is adapted for operation in the input voltage range from 220 to 240 V AC and 50/60 Hz frequency. It has IP67 leak class, which guarantees resistance to water and dust.



**Technical data**

Parameter	Value
Warranty	5/7*
Power	• 200 W
Voltage	• 220-240 V AC
IP protection rating	IP67
IEC protection class	I
Output current range	0 ÷ 16.67A
Wire length	200 mm
Input voltage frequency range	50 ÷ 60Hz
Safety standards	IP67
Efficiency	0,84
Voltage tolerance	-/+0.5V

Parameter	Value
Ambient humidity	20 ÷ 90%
Insulation strength	3kVAC
EMC standards	EN55015
Mounting type	surface
Inrush current (typ.)	30A / 230VAC
Frequency of the supply voltage	50/60Hz
Power Factor	0,95
Ambient temperature suitable for operation	-25÷40
Height	22
Output voltage	• 12 V


LED line PRIME

Code: LL-200-12-ALU

EAN: 5905378217973

**Power Supply 200-12 IP67 200W 12V  
Aluminum PRIME**

**Technical drawing**



**Light distribution**

**Additional product photos**



**Logistics data**



**Single packaging**

Quantity	1
Width	54 mm
Height	30 mm
Length	335 mm
Weight	0,696 kg

**Bulk packaging**

Quantity	30
Width	275 mm
Height	215 mm
Length	350 mm
Weight	20,88 kg

**Europallet**

Quantity	1260
Height	1505 mm
Bulk quantity	42
Weight	876 kg

---

LED line PRIME

Code: LL-200-12-ALU

EAN: 5905378217973

**Power Supply 200-12 IP67 200W 12V  
Aluminum PRIME**

---

**Example application**