

LED line LITE

Code: 244506

EAN: 5901583244506

**LED bulb G4 3000K 2W 220lm 12V DC  
270° Silicone LITE**



LEDOM G4 2W 3000K LED line LITE bulb is a perfect combination of energy savings and high performance. Powered by 12V DC voltage, emitting a warm light at 3000 K, it creates a cozy atmosphere. A light stream of 220 lm and a light angle of 270° ensure effective light scattering. Thanks to SMD3014 diodes, it achieves light efficiency of 110 lm/W.



**Technical data**

Parameter	Value
Energy efficiency class 2019/2015	F
Warranty	3
Power	• 2 W
Voltage	• 12 V DC
Correlated colour temperature	• 3000 K
Colour of the light	White
Colour rendering index Ra	80
Luminous efficacy	110
Luminous flux	220 lm
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
L80B* – difference B10–B50 ≈ 1% (according to LightingEurope) – negligible	35000 h

Parameter	Value
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	270 °
Lifespan	50 000 h
Number of on/off cycles	50000
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	37
Fixture's diameter	13 mm
Material (housing)	Silicone


LED line LITE

Code: 244506

EAN: 5901583244506

**LED bulb G4 3000K 2W 220lm 12V DC  
270° Silicone LITE**

**Technical drawing**






**Light distribution**

**Additional product photos**



**Logistics data**



**Single packaging**

Quantity	1
Width	20 mm
Height	20 mm
Length	62 mm
Weight	0,005 kg

**Bulk packaging**

Quantity	500
Width	610 mm
Height	235 mm
Length	150 mm
Volume	0,021 m3
Weight	4,285 kg
Comments	

**Europallet**

Quantity	54000
Height	1880 mm
Quantity in layer	4000
Number of layers	8
Bulk quantity	32000
Weight	182,4 kg

---

LED line LITE

Code: 244506

EAN: 5901583244506

**LED bulb G4 3000K 2W 220lm 12V DC  
270° Silicone LITE**

---

**Example application**