


# LEDOM G4 2W 3000K 220lm 12V DC 24 SMD3014 SL



Beam angle



Ambient temperature suitable for operation



Voltage range and voltage type




Lifespan

Parameter	Value
Luminous efficacy	110 lm/W
Colour of the light	White
Energy efficiency class 2019/2015	F
Luminous flux	220 lm
Colour consistency in McAdam ellipses	≤6
Warranty (years)	2
Survival factor	0.9
Lifetime L70B50	50 000
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
The lumen maintenance factor	96 %
Lamp's diameter	13


Parameter	Value
Beam angle	270 °
Lifespan	50000
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷40 °C
For indoor use	Inside
Height	37 mm
Product weight with packaging	5 g
Energy class	A+
Power	• 2 W
Voltage	• 12 V DC
Correlated colour temperature	• 3000 K

**Single packaging**




Width	20 mm
Height	20 mm
Length	62 mm
Weight	0,005 kg
	1

**Bulk packaging**



Number of pieces/tape in meters pack zb	500 szt.
Width	610 mm
Height of collective packaging	235 mm
Length	150 mm
Weight	2,85 kg
Volume	0,021 m <sup>3</sup>

**Europallet**



Number of pieces/tapes in meters euro pallet	54000
Quantity collective euro pallet	32000 szt.
Weight of a euro pallet	182,4 kg
Pallet height	1880 mm
Quantity in 1 layer	4000 szt.
Number of layers	8