

LED line PRIME

Code: 203105

EAN: 5905378203105

**Road luminaire CAMINO 4000K 50W
7000lm IP66 grey PRIME**



CAMINO 50W LED line PRIME is an innovative lighting solution that stands out with a power of 50 W and a light stream of 7000 lumens. Thanks to high light efficiency of 140 lm/W and the use of LUMILEDS LEDs, it guarantees reliable operation. It offers neutral colour temperature 4000 K and IP66 leak classification provides resistance to adverse weather conditions.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	C
Warranty	5/7*
Power	• 50 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	70
IP protection rating	IP66
IK protection rating	08
IEC protection class	I
Luminous efficacy	140
Luminous flux	7000
The lumen maintenance factor	96
Lifetime L70B50	100 000 h
L80B* – difference B10–B50 ≈ 1% (according to LightingEurope) – negligible	75000 h

Parameter	Value
L90B* – difference B10–B50 ≈ 1% (according to LightingEurope) – negligible	50000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
ULOR	0 %
Frequency of the supply voltage	50/60Hz
Beam angle	150 x 110
LED type	LUMILEDS 2835
LED quantity	96
Power Factor	0,9
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-40÷50
Material (housing)	Die cast aluminium
Material (cover)	Tempered glass
Lifetime L80B10	75 000


LED line PRIME

Code: 203105


EAN: 5905378203105

**Road luminaire CAMINO 4000K 50W
7000lm IP66 grey PRIME**

Technical drawing






Light distribution



Additional product photos



Logistics data



Single packaging

Width	236 mm
Height	116 mm
Length	560 mm
Weight	2,3 kg

Bulk packaging

Quantity	1
Width	236 mm
Height	116 mm
Length	560 mm
Volume	15,33 m ³
Weight	2,3 kg

Europallet

Quantity	90
Height	1,90 m
Quantity in layer	30
Number of layers	3
Bulk quantity	90
Weight	232 kg

LED line PRIME

Code: 203105

EAN: 5905378203105

**Road luminaire CAMINO 4000K 50W
7000lm IP66 grey PRIME**

Example application

