


LED line PRIME Road luminaire CAMINO 50W 4000K 7000lm



One of the key factors investors look at when choosing outdoor lighting, including street lighting, is power. That's why CAMINO luminaires are **available in four power options: 50W, 100W, 150W and 200W**. Equipped with LUMILEDS 2835 LEDs and other carefully selected and quality-tested components, they ensure **reliable operation** and long life of the luminaires, which translates into **reduced maintenance and component replacement needs**.

CAMINO are luminaires designed for harsh weather conditions. Appropriate construction (**IP66 degree of protection**) and the use of high-quality materials, such as tempered glass diffuser and cast aluminum housing, guarantee resistance to external factors such as rain, wind and changing temperatures.

The luminaires are **guaranteed for 5 years**, which means that for such a long time the investor does not have to bear the costs associated with any repairs or replacement of lighting. This is important, especially for large projects, where the cost of maintaining the lighting infrastructure can be significant. The lifespan of the luminaire marked as L50B70 - 100 000h in practice means that after a certain period of operation, at least 50% of the diodes in the luminaire will continue to shine with a brightness of at least 70% of their initial value.

Customized versions for Zhaga standards and NEMA sockets available upon request.



Manufacturer issues a 5-year warranty for this product.



Voltage range and voltage type



Motion detection angle



Lifespan



Dimmable



Beam angle



Ambient temperature suitable for operation



LED type




LED quantity

Parameter	Value
ULOR	0 %
Luminous efficacy	140 lm/W
Power	50 W
Colour of the light	White
Energy efficiency class 2019/2015	C
Luminous flux	7000 lm
Correlated colour temperature	4000 K
Colour consistency in McAdam ellipses	≤6
IP protection rating	66
Warranty (years)	5

Parameter	Value
Beam angle	150 x 110 °
Material (cover)	tempered glass
Material (housing)	aluminum
LED type	LUMILEDS 2835
LED quantity	96
Power Factor	0,9
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-40+50 °C
For indoor and outdoor use	YES
IEC protection class	I


Survival factor	0.9	IK protection rating	08
Lifetime L70B50	100 000	Lamp's warm-up time to 60%	1
Supply voltage range and voltage type	220-240 VAC	Length	514 mm
Frequency of the supply voltage	50/60Hz	Width	200 mm
Colour rendering index Ra	70	Height	80 mm
The lumen maintenance factor	96 %		

Single packaging




Width 514 mm
 Height 80 mm
 Length 200 mm
 Weight 2,3 kg

Bulk packaging



Number of pieces/tape in meters pack 1 szt.
 zb
 Width 5600 mm
 Height of collective packaging 1160 mm
 Length 2360 mm
 Weight
 Volume 15,33 m³

Europallet



Quantity collective euro pallet 96
 Weight of a euro pallet 330,4 kg
 Pallet height 184 cm
 Number of layers 1