


LED line LITE Floodlight PHOTON 50W 4000K 5000lm with motion sensor



Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.



Manufacturer issues a 3-year warranty for this product.



Beam angle



Ambient temperature suitable for operation



Lifespan



This product is featured by a high degree of IP protection, which makes it suitable for a broader range of lighting applications and offers high safety of use.



The structural design of this product ensures effective heat dissipation.



Voltage range and voltage type




LED type




LED quantity

Parameter	Value
Luminous efficacy	100 lm/W
Power	50 W
Colour of the light	White
Wyniki tłumaczenia Functional description of the daylight sensor [LUX]	Min 5 lx - Max 2000 lx
Energy efficiency class 2019/2015	F
Luminous flux	5000 lm
Correlated colour temperature	4000 K
Colour consistency in McAdam ellipses	≤6
IP protection rating	65
Warranty (years)	3
Survival factor	0.9
Lifetime L70B50	30 000
Rated power	220-240V AC
Weight	560 g
Mounting type	surface
Mounting height	2.3-5.0m
Supply voltage range and voltage type	220-240 VAC
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80


Parameter	Value
Colour	Black
The lumen maintenance factor	96 %
Beam angle	120 °
Sensor type	PIR
Material (cover)	tempered glass
Material (housing)	DIE-CAST alu
LED type	SMD2835
LED quantity	75
Power Factor	0,9
Number of on/off cycles	18000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷40 °C
For indoor and outdoor use	YES
IEC protection class	I
IK protection rating	05
Lamp's warm-up time to 60%	1
Length	191 mm
Width	64 mm
Height	210 mm

Single packaging

Width	191 mm
Height	210 mm
Length	64 mm
Weight	0,57 kg
	1

Bulk packaging

Number of pieces/tape in meters pack zb	12 szt.
Width	488 mm
Height of collective packaging	230 mm
Length	417 mm
Weight	7,19 kg
Volume	0,046 m ³

Europallet

Quantity collective euro pallet	192 szt.
Weight of a euro pallet	115,04 kg
Pallet height	1840 mm
Quantity in 1 layer	24 szt.
Number of layers	8