

LED line LITE

Code: 248320

EAN: 5901583248320

**LED bulb GU10 6500K 5W 410lm 230V
50° Glass LITE**



LITE GU10 5W 6500K LED line bulb is an efficient light source that generates a bright stream of 410 lumens at only 5 watts, which translates into 82 lm/W efficiency. It is characterized by a cool light colour at 6500 K and colour stability (MacAdam Steps ≤ 6). Ra color reproduction factor at level 80 provides natural color rendering. Life is as high as 30,000 hours, and the lighting angle is 50°.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	G
Warranty	3
Power	• 5 W
Voltage	• 220-260 V AC
Correlated colour temperature	• 6500 K
Colour of the light	White
Colour rendering index Ra	80
Luminous efficacy	82
Luminous flux	410 lm
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤ 6

Parameter	Value
Frequency of the supply voltage	50/60Hz
Beam angle	50°
LED type	SMD2835
Power Factor	0,4
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	53
Fixture's diameter	50 mm
Material (housing)	Glass
Material (cover)	glass

LED line LITE


Code: 248320

EAN: 5901583248320

**LED bulb GU10 6500K 5W 410lm 230V
50° Glass LITE**




Technical drawing

Light distribution



Additional product photos

Logistics data



Single packaging

Quantity	10
Width	50 mm
Height	50 mm
Length	60 mm
Weight	0,07 kg

Bulk packaging

Quantity	100
Width	290 mm
Height	170 mm
Length	595 mm
Volume	0,029 m3
Weight	6,5 kg
Comments	

Europallet

Quantity	4500
Height	1870 mm
Quantity in layer	400
Number of layers	11
Bulk quantity	4400
Weight	286 kg

LED line LITE

Code: 248320

EAN: 5901583248320

**LED bulb GU10 6500K 5W 410lm 230V
50° Glass LITE**

Example application