

LED line LITE

Code: 244742

EAN: 5901583244742

**LED bulb GU10 4000K 7W 600lm 230V
120° PC LITE**



LITE GU10 LED line bulb with 7W power and 600 lm light stream, with 4,000 K light colour, is a modern light source characterized by high energy efficiency of 85 lm/W. Thanks to the durability of up to 50,000 hours (L70B50) and Ra color reproduction factor of 80, it provides faithful color rendering. A wide lighting angle of 120° allows even lighting of the rooms.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	F
Warranty	3
Power	• 7 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
Luminous efficacy	85
Luminous flux	600 lm
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
L80B* – difference B10–B50 ≈ 1% (according to LightingEurope) – negligible	35000 h

Parameter	Value
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	120 °
Lifespan	50 000 h
Power Factor	>=0,5
Number of on/off cycles	50000
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	56 mm
Material (housing)	Polycarbonate

LED line LITE


Code: 244742

EAN: 5901583244742

**LED bulb GU10 4000K 7W 600lm 230V
120° PC LITE**

Technical drawing



Light distribution



Additional product photos



Logistics data



Single packaging

Quantity	1
Width	650 mm
Height	30 mm
Length	30 mm
Weight	0,03 kg

Bulk packaging

Quantity	100
Width	270 mm
Height	140 mm
Length	525 mm
Volume	0,019 m3
Weight	4 kg
Comments	

Europallet

Quantity	6000
Height	1,90 m
Quantity in layer	
Number of layers	
Bulk quantity	60
Weight	280 kg

LED line LITE

Code: 244742

EAN: 5901583244742

**LED bulb GU10 4000K 7W 600lm 230V
120° PC LITE**

Example application