


**LEDOM GU10 7W 4000K 600lm 220-240V**

Manufacturer issues a 3-year warranty for this product.



Beam angle



Ambient temperature suitable for operation



Voltage range and voltage type




Lifespan

Parameter	Value
Luminous efficacy	85 lm/W
Power	7 W
Colour of the light	White
Energy efficiency class 2019/2015	F
Luminous flux	600 lm
Correlated colour temperature	4000 K
Colour consistency in McAdam ellipses	≤6
Warranty (years)	3
Survival factor	0.9
Lifetime L70B50	50 000
Supply voltage range and voltage type	220-240 VAC
Frequency of the supply voltage	50/60Hz

Parameter	Value
Colour rendering index Ra	80
The lumen maintenance factor	96 %
Lamp's diameter	50
Beam angle	120 °
Lifespan	50000
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷40 °C
For indoor use	Inside
Height	56 mm
Energy class	A+


Luminous [cd/klm]



C0 - C180 C90 - C270


8519\_248672\_33508\_0\_20190518\_8\_0161

Single packaging




Width	650 mm
Height	30 mm
Length	30 mm
Weight	0,03 kg
	1

Bulk packaging



Number of pieces/tape in meters pack zb	100 szt.
Width	525 mm
Height of collective packaging	140 mm
Length	270 mm
Weight	4 kg
	0,019
Volume	m3

Europallet



Number of pieces/tapes in meters euro pallet	4400
Quantity collective euro pallet	5200 szt.
Weight of a euro pallet	208 kg
Pallet height	1820 mm
Quantity in 1 layer	400 szt.
Number of layers	13