

LED line LITE Code: 200876 EAN: 5905378200876

LED line LITE Downlight MOLLY 18W 1750lm 3000K square





The 18W Downlight MOLLY LED setting is characterized by a modern and minimalist design, which perfectly fits in a variety of interiors. It offers a light stream of 1750 lm and a colour temperature of 3000 K, which provides pleasant, warm light. IP20 leak class protects against dust and Ra>80 colour reproduction factor guarantees natural color rendering.

















Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	3
Power	• 18 W
Voltage	• 170-260 V AC
Correlated colour temperature	• 3000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IEC protection class	II
Luminous efficacy	100
Luminous flux	1750
The lumen maintenance factor	96
Lifetime L70B50	30 000 h


Parameter	Value
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
LED type	SMD LED 2835
LED quantity	72
Power Factor	0,5
Number of on/off cycles	20000
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Mounting hole diameter	140-160
Colour	White
Material (housing)	Polycarbonate



LED line LITE Code: 200876 EAN: 5905378200876


LED line LITE Downlight MOLLY 18W 1750lm 3000K square

Technical drawing




Light distribution

Luminous [cd/klm]



Additional product photos












Logistics data







Single packaging

Bulk packaging

Europallet



LED line LITE Code: 200876 EAN: 5905378200876

LED line LITE Downlight MOLLY 18W 1750lm 3000K square

Example application

