

LED line LITE

Code: 207479

EAN: 5905378207479

Park Luminaire PARKLITE 80-100-120W
CCT 9600-14400lm black LITE

New



Technical data

Parameter	Value	Parameter	Value
ULOR	2,3 %	Material (housing)	aluminum
Luminous efficacy	120 lm/W	LED type	SMD LED 2835
Colour of the light	White	LED quantity	384
Energy efficiency class 2019/2015	E	Power Factor	0,9
Luminous flux	9600-14400 lm	Colour consistency in McAdam ellipses	≤6
Colour consistency in McAdam ellipses	≤6	Ambient temperature suitable for operation	-30÷50 °C
IP protection rating	IP65	For indoor and outdoor use	YES
Survival factor	0.9	IEC protection class	I
Lifetime L70B50	25 000	IK protection rating	08
Wire length	400 mm	Full box quantity	6 pc
Weight	2190 g	Lamp's warm-up time to 60%	1
Frequency of the supply voltage	50/60Hz	Height	117 mm
Colour rendering index Ra	80	Power	• 80 W • 100 W • 120 W
Colour	96	Voltage	• 220-240 V AC
Beam angle	100 °	Correlated colour temperature	• 3000 K • 4000 K • 6000 K
Material (cover)	tempered glass		

LED line LITE


Code: 207479

EAN: 5905378207479

Park Luminaire PARKLITE 80-100-120W
CCT 9600-14400lm black LITE

Dimensions


Light distribution



Additional product photos




Logistics data




Single packaging

Width	420 mm
Height	135 mm mm
Length	425 mm mm
Weight	2,25 kg kg



Bulk packaging

Number of pieces/tape in meters pack zb	4 szt.
Width	550 mm
Height of collective packaging	445 mm
Length	430 mm
Weight	9,3 kg
Volume	0,105 m3



Europallet

Quantity collective euro pallet	32 szt.
Weight of a euro pallet	74,4 kg
Pallet height	1780 mm
Quantity in 1 layer	8 szt.
Number of layers	4

LED line LITE

Code: 207479

EAN: 5905378207479

**Park Luminaire PARKLITE 80-100-120W
CCT 9600-14400lm black LITE**

Example application