

LED line LITE

Code: 207479

EAN: 5905378207479

**Park luminaire PARKLITE 3CCT(3/4/6K)
80-100-120W 9600-14400lm IP65 black
LITE**



PARKLITE 80-120W park mount combines modern LED technology with elegant black finish. Its impressive light stream of 9600 to 14400 lumens provides excellent lighting under different conditions. The device is characterized by a class of protection IP65 and IK08, which guarantees resistance to adverse weather conditions and mechanical damage.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Power	<ul style="list-style-type: none"> • 80 W • 100 W • 120 W
Voltage	<ul style="list-style-type: none"> • 220-240 V AC
Correlated colour temperature	<ul style="list-style-type: none"> • 3000 K • 4000 K • 6000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP65
IK protection rating	08
IEC protection class	I
Luminous efficacy	120
Luminous flux	9600-14400
Lifetime L70B50	25 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6

Parameter	Value
ULOR	2,3%
Wire length	400 mm
Frequency of the supply voltage	50/60Hz
Beam angle	100
LED type	SMD LED 2835
LED quantity	384
Power Factor	0,9
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-30÷50
Height	117
Colour	96
Material (housing)	Aluminium
Material (cover)	Tempered glass


LED line LITE

Code: 207479


EAN: 5905378207479

**Park luminaire PARKLITE 3CCT(3/4/6K)
80-100-120W 9600-14400lm IP65 black
LITE**

Technical drawing






Light distribution



Additional product photos



Logistics data



Single packaging

Width	420 mm
Height	135 mm
Length	425 mm
Weight	2,25 kg

Bulk packaging

Quantity	4
Width	445 mm
Height	430 mm
Length	550 mm
Volume	0,105 m ³
Weight	9,3 kg

Europallet

Height	1780 mm
Quantity in layer	8
Number of layers	4
Bulk quantity	32
Weight	74,4 kg

LED line LITE

Code: 207479

EAN: 5905378207479

**Park luminaire PARKLITE 3CCT(3/4/6K)
80-100-120W 9600-14400lm IP65 black
LITE**

Example application

