

LED line PRIME


Code: 247606-II

EAN: 5905378201767

**LED bulb E27 4000K 7W 1000lm 230V
220° G45 DIM Ceramic PRIME**



LED bulb E27 7W 4000K 1000lm from LED line PRIME is an innovative light source that guarantees high performance of 142 lm/W. By emitting neutral white light with a colour temperature of 4000 K, it provides pleasant lighting without flickering effect and with minimal brightness loss after long-term use (96% light stream). Persistence reaches 30,000 hours, and the number of activation cycles is as high as 50,000.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5
Power	• 7 W
Voltage	• 170-250 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
Luminous efficacy	142
Luminous flux	1000 lm
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9
Dimmable function	PWM
Colour consistency in McAdam ellipses	≤6

Parameter	Value
Frequency of the supply voltage	50/60Hz
Lamp's type	G45
Beam angle	220 °
LED type	SMD2835
Power Factor	0,5
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	84
Fixture's diameter	45 mm
Colour	White
Material	Ceramic
Material (housing)	Ceramics
Material (cover)	glass


LED line PRIME

Code: 247606-II


EAN: 5905378201767

**LED bulb E27 4000K 7W 1000lm 230V
220° G45 DIM Ceramic PRIME**

Technical drawing






Light distribution



Additional product photos



Logistics data



Single packaging

Quantity	1
Width	50 mm
Height	63 mm
Length	50 mm
Weight	0,06 kg

Bulk packaging

Quantity	100
Width	270 mm
Height	230 mm
Length	530 mm
Volume	0,032 m3
Weight	7 kg

Europallet

Height	1840 mm
Quantity in layer	400
Number of layers	8
Bulk quantity	3200
Weight	224 kg

LED line PRIME

Code: 247606-II

EAN: 5905378201767

**LED bulb E27 4000K 7W 1000lm 230V
220° G45 DIM Ceramic PRIME**

Example application