




code: LL-75-12 EAN: 5907777479228

LED power supply LED line PRIME LL-75-12 IP67 12V

Waterproof switching power supplies of the LL series by LED line will prove themselves in many, even the most demanding applications. They are characterized by small dimensions, low weight, and thanks to the installation holes, they are easy to install.

- Constant voltage power supply
- Universal input voltage range
- Protections: Short circuit / Overcurrent / Overvoltage
- Free air cooling
- Full load tested
- Protection class II, power class 2 according to UL1310
- Degree of protection IP67




Ambient temperature suitable for operation

Parameter	Value
Output power	72W
Output voltage	12V
Output current range	0 ÷ 6A
Warranty (years)	5
Input voltage range	90 ÷ 264V AC
Input voltage frequency range	47 ÷ 63Hz
Rated current	6A
Safety standards	IP67
Efficiency	0,84


Parameter	Value
Voltage tolerance	-/+5,0%
Ambient humidity	20 ÷ 90%
Insulation strength	3kVAC
EMC standards	EN55015
Mounting type	surface
Inrush current (typ.)	70A / 230VAC
Ambient temperature suitable for operation	-30÷70 °C
IEC protection class	II

Single packaging




Width 52 mm
Height 35 mm
Length 185 mm
Weight 0,4 kg
1

Bulk packaging



Outer box quantity 50
Width 275 mm
Length 195
Weight 385 mm
21 kg

Europallet



Weight of a euro pallet 48
1018 kg
1200