

LED line PRIME

Code: 203273

EAN: 5905378203273

**Linear luminaire FUSION 4000K 60W
7800lm 120° IP20 150cm white PRIME
PC Cover**



The 60W and 7800 lm FUSION linear housing provides optimal light scattering with an angle of 120°. It is characterized by a colour temperature of 4000K, which facilitates the creation of a pleasant atmosphere in the rooms. Made of durable aluminum, it guarantees longevity and effective heat discharge. IP20 leak class and IK08 indicator show product reliability.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	C
Warranty	5/7*
Power	• 60 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IEC protection class	I
Luminous efficacy	130
Luminous flux	7800
The lumen maintenance factor	96
Lifetime L70B50	50 000 h

Parameter	Value
L80B* – difference B10–B50 ≈ 1% (according to LightingEurope) – negligible	35000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
Sling length	200 cm
Standby power	0
Mounting type	mixed
Frequency of the supply voltage	50/60Hz
Beam angle	120
Power Factor	0,9
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷45
For indoor use	Inside
Height	52


LED line PRIME

Code: 203273


EAN: 5905378203273

**Linear luminaire FUSION 4000K 60W
7800lm 120° IP20 150cm white PRIME
PC Cover**

Technical drawing






Light distribution



Additional product photos



Logistics data



Single packaging

Width	1444 mm
Height	52 mm
Length	70 mm
Weight	1,97 kg

Bulk packaging

Quantity	12
Width	1550 mm
Height	260 mm
Length	260 mm
Volume	0,104 m3
Weight	22,6 kg
Comments	

Europallet

Quantity	144
Height	1550 mm
Quantity in layer	144
Number of layers	1
Bulk quantity	144
Weight	286,8 kg

LED line PRIME

Code: 203273

EAN: 5905378203273

**Linear luminaire FUSION 4000K 60W
7800lm 120° IP20 150cm white PRIME
PC Cover**

Example application