

LED line PRIME

Code: 205970-DALI

EAN: 5905378220065

Panel Backlit 25W 4000K 4000lm  
60x60 DALI PRIME



The PRIME 25W LED line panel is an innovative 595x595 mm ceiling luminaire, characterized by high quality workmanship and even light distribution. Thanks to the use of SMD LEDs 2835, the panel generates a light stream of 4000 lm at 160 lm/W efficiency. The light colour is 4000 K, providing neutral lighting. The housing guarantees a longevity of 50.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	C
Warranty	5
Power	• 25 W
Voltage	• 200-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	02
IEC protection class	II
Luminous efficacy	160
Luminous flux	4000
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
Survival factor	0.9

Parameter	Value
Dimmable function	PWM
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	120
LED type	SMD LED 2835
LED quantity	96
Power Factor	0.9
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Colour	white
Material (housing)	Aluminium
Material (cover)	Polystyrene

LED line PRIME

Code: 205970-DALI

EAN: 5905378220065

**Panel Backlit 25W 4000K 4000lm  
60x60 DALI PRIME**


Technical drawing

Light distribution


Additional product photos




Logistics data



Single packaging



Bulk packaging



Europallet

LED line PRIME

Code: 205970-DALI

EAN: 5905378220065

**Panel Backlit 25W 4000K 4000lm  
60x60 DALI PRIME**

**Example application**

