

LED line® GU10 1W 3000K 80lm 220-260V

Product is offered in the choice of 7 colours.



Manufacturer issues a 3-year warranty for this product.



Beam angle



Lifespan



High user-safety guaranteed.



Voltage range and voltage type




LED type




Parameter	Value
Luminous efficacy	80 lm/W
Power	1 W
Colour of the light	White
Energy efficiency class 2019/2015	G
Luminous flux	80 lm
Correlated colour temperature	3000 K
Colour consistency in McAdam ellipses	≤6
Warranty (years)	3
Dimmable function	No
Survival factor	0.9
Lifetime L70B50	30 000
Supply voltage range and voltage type	220-260 AC
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
The lumen maintenance factor	96
Lamp's diameter	50
Beam angle	120 °
Material (cover)	glass
Material (housing)	Glass
LED type	SMD2835
Lifespan	30000
Number of on/off cycles	50000


Parameter	Value
Colour consistency in McAdam ellipses	≤6
For indoor use	Inside
Full box quantity	100 pc
Lamp's warm-up time to 60%	1
Height	55 mm
Product weight with packaging (g)	56 g
Master carton weight (kg)	5,6
EPREL ID	632 148
Date of first placement on the market	01.01.2021
Energy class	A++
Angle for useful luminous flux (EPREL)	Wide cone of 120 degrees
Is the product equipped with an integrated light source? (EPREL)	No
Non-directional or directional light source (EPREL)	DLS
Is this product a light source? (EPREL)	Yes
Mains or non- mains light source (EPREL)	MLS
Connected light source (EPREL)	No
Colour-tuneable light source (EPREL)	No
R9 colour rendering index value (EPREL)	4
Total luminous flux (EPREL)	80
On-mode power Pon (EPREL)	1
Useful luminous flux Φuse (EPREL)	60
Beam angle in degrees (EPREL)	120



Single packaging



Bulk packaging



Europallet

