

code: 241505 EAN: 5901583241505

LED line® strip 300 SMD 12V green 4,8W IP67



LED Strip line is a modern and versatile linear **light source**, used for interior lighting, furniture, lightboxes, illuminated signs, and public spaces.





Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.



Yellow free technology means that the housing of this product is made of high quality material which is resistant to yellowing degeneration caused by UV radiation, thanks to which the product maintains its easthetic appearance for many years.



This product is featured by a high degree of IP protection, which makes it suitable for a broader range of lighting applications and offers high safety of use.



Manufacturer issues a 3-year warranty for this product.



Voltage range and voltage type



Beam angle



Ambient temperature suitable for operation



LED type



Lifespan



LED quantity (1m)




Dimmable

| Parameter | Value |
|---------------------------------------|---------|
| Colour of the light | Green |
| IP protection rating | 67 |
| Warranty (years) | 3 |
| Minimum purchase quantity | 5 |
| Lifetime L70B50 | 30 000 |
| Wattage (lm) | 4,8 W |
| Current (lm) | 0,4 |
| Supply voltage range and voltage type | 12 DC |
| Metres per roll | 5 |
| The lumen maintenance factor | >0,7 |
| Beam angle | 120 ° |
| LED type | SMD3528 |
| Not dimmable | TAK |
| Compatible dimmer type | PWM |
| Laminate (colour) | White |
| Laminate (thickness) | 2 |


| Parameter | Value |
|--|--------------|
| LED quantity (Im) | 60 |
| Cutting section | 5 |
| Type of adhesive tape | Piankowa |
| Lifespan | 100000 |
| Number of on/off cycles | 50000 |
| Colour consistency in McAdam ellipses | ≤ 3 |
| Ambient temperature suitable for operation | `-20 ÷ 45 °C |
| For indoor and outdoor use | YES |
| IEC protection class | III |
| Full box quantity | 40 pc |
| Lamp's warm-up time to 60% | 1 |
| Width | 10 mm |
| Height | 5 mm |
| Product weight with packaging (g) | 301 g |
| Master carton weight (kg) | 12,04 |



Single packaging



Bulk packaging



Europallet

