

LED line PRIME

Code: 219229

EAN: 5905378219229


Highbay luminaire PHANTOM 4000K  
200W 35000lm 60° IP65 CRI80 black  
PRIME 1-10V



**Phantom PRIME** is a high-performance high-bay fixture that combines energy efficiency, reliability, and ease of installation. Designed for halls, warehouses, sports facilities, and food-pharmaceutical plants, it guarantees excellent working conditions and quick amortization.

Key attributes:

- Power 70 W / 100 W / 150 W / 200 W, efficiency up to 190 lm/W (CRI 70) or 175 lm/W (CRI 80)
- Adjustable beam angles 60° / 90° / 120° for precise illumination
- PZH certificate – approved for environments with strict hygiene standards
- IP65 & IK08 resistance, operating temperatures from -30 °C to +45 °C
- Lightweight aluminum housing – quick and safe installation at height
- 5 years warranty\* – full service support
- **Product made to order - delivery within 7 days.**



Technical data

| Parameter                         | Value          |
|-----------------------------------|----------------|
| Energy efficiency class 2019/2015 | B              |
| Warranty                          | 5/7*           |
| Power                             | • 200 W        |
| Voltage                           | • 100-277 V AC |
| Correlated colour temperature     | • 4000 K       |
| Colour of the light               | White          |
| Colour rendering index Ra         | 80             |
| IP protection rating              | IP65           |
| IK protection rating              | 09             |
| IEC protection class              | I              |
| Luminous efficacy                 | 175            |
| Luminous flux                     | 35000          |
| The lumen maintenance factor      | 96             |

| Parameter                                  | Value     |
|--------------------------------------------|-----------|
| Lifetime L70B50                            | 100 000 h |
| Dimmable function                          | 1-10      |
| Frequency of the supply voltage            | 50/60Hz   |
| Beam angle                                 | 60        |
| LED type                                   | SMD 2835  |
| LED quantity                               | 640       |
| Power Factor                               | >=0,95    |
| Number of on/off cycles                    | 50000     |
| Lamp's warm-up time to 60%                 | 1         |
| Ambient temperature suitable for operation | -30÷45    |
| Height                                     | 156 mm    |
| Fixture's diameter                         | 330 mm    |
| Material (housing)                         | Aluminium |


LED line PRIME

Code: 219229

EAN: 5905378219229


Highbay luminaire PHANTOM 4000K  
200W 35000lm 60° IP65 CRI80 black  
PRIME 1-10V

Technical drawing






Light distribution

Additional product photos



Logistics data



Single packaging

|          |        |
|----------|--------|
| Quantity | 1      |
| Width    | 380 mm |
| Height   | 380 mm |
| Length   | 170 mm |
| Weight   | 2,4 kg |

Bulk packaging

|          |          |
|----------|----------|
| Quantity | 1        |
| Width    | 380 mm   |
| Height   | 170 mm   |
| Length   | 380 mm   |
| Volume   | 0,024 m3 |
| Weight   | 2,4 kg   |

Europallet

|                   |         |
|-------------------|---------|
| Quantity          | 66      |
| Height            | 1870 mm |
| Quantity in layer | 6       |
| Number of layers  | 11      |
| Bulk quantity     | 66      |
| Weight            | 25 kg   |



LED line PRIME

Code: 219229

EAN: 5905378219229

**Highbay luminaire PHANTOM 4000K  
200W 35000lm 60° IP65 CRI80 black  
PRIME 1-10V**

**Example application**

