

LED line LITE

Code: 205598

EAN: 5905378205598

**Backlit Panel 2in1 4000K 40W 4000lm
IP20 62x62cm white Surface-
mounted/Recessed LITE**



The 2in1 Backlit Panel with a power of 40 W and a color temperature of 4000 K is an excellent solution in the field of lighting. Emitting a luminous flux of 4000 lm, it provides an efficiency of 100 lm/W. The backlit design ensures even light distribution, while the housing made of metal and polystyrene is resistant to deformation. With an IP20 ingress protection rating and a UGR<22 index, the product offers high visual comfort.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	3
Power	• 40 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	02
IEC protection class	I
Luminous efficacy	100
Luminous flux	4000
The lumen maintenance factor	96

Parameter	Value
Lifetime L70B50	30 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	120
Power Factor	0,9
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	38 mm
Material (housing)	Metal
Material (cover)	Polystyrene


LED line LITE

Code: 205598

EAN: 5905378205598

**Backlit Panel 2in1 4000K 40W 4000lm
IP20 62x62cm white Surface-
mounted/Recessed LITE**

Technical drawing






Light distribution

Additional product photos



Logistics data



Single packaging

Width	630 mm
Height	45 mm
Length	630 mm
Weight	1,67 kg

Bulk packaging

Quantity	6
Width	645 mm
Height	300 mm
Length	655 mm
Volume	0,128 m ³
Weight	10,32 kg

Europallet

Height	1820 mm
Quantity in layer	24
Number of layers	2
Bulk quantity	48
Weight	82,56 kg

LED line LITE

Code: 205598

EAN: 5905378205598

**Backlit Panel 2in1 4000K 40W 4000lm
IP20 62x62cm white Surface-
mounted/Recessed LITE**

Example application