


## LED line PRIME Road luminaire CAMINO 200W 4000K 28000lm



One of the key factors investors look at when choosing outdoor lighting, including street lighting, is power. That's why CAMINO luminaires are **available in four power options: 50W, 100W, 150W and 200W**. Equipped with LUMILEDS 2835 LEDs and other carefully selected and quality-tested components, they ensure **reliable operation** and long life of the luminaires, which translates into **reduced maintenance and component replacement needs**.

CAMINO are luminaires designed for harsh weather conditions. Appropriate construction (**IP66 degree of protection**) and the use of high-quality materials, such as tempered glass diffuser and cast aluminum housing, guarantee resistance to external factors such as rain, wind and changing temperatures.

The luminaires are **guaranteed for 5 years**, which means that for such a long time the investor does not have to bear the costs associated with any repairs or replacement of lighting. This is important, especially for large projects, where the cost of maintaining the lighting infrastructure can be significant. The lifespan of the luminaire marked as L50B70 - 100 000h in practice means that after a certain period of operation, at least 50% of the diodes in the luminaire will continue to shine with a brightness of at least 70% of their initial value.

Customized versions for Zhaga standards and NEMA sockets available upon request.



Manufacturer issues a 5-year warranty for this product.



Beam angle



Voltage range and voltage type



Ambient temperature suitable for operation



Motion detection angle



LED type



Lifespan



LED quantity



Dimmable

Parameter	Value
ULOR	0 %
Luminous efficacy	140 lm/W
Power	200 W
Colour of the light	White
Energy efficiency class 2019/2015	D
Luminous flux	28000 lm
Correlated colour temperature	4000 K
Colour consistency in McAdam ellipses	≤6
IP protection rating	66
Warranty (years)	5

Parameter	Value
Beam angle	150 x 110 °
Material (cover)	tempered glass
Material (housing)	aluminum
LED type	LUMILEDS 2835
LED quantity	320
Power Factor	0,9
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-40+50 °C
For indoor and outdoor use	YES
IEC protection class	I

Survival factor	0.9	IK protection rating	08
Lifetime L70B50	100 000	Lamp's warm-up time to 60%	1
Supply voltage range and voltage type	220-240 VAC	Length	665 mm
Frequency of the supply voltage	50/60Hz	Width	290 mm
Colour rendering index Ra	70	Height	84 mm
The lumen maintenance factor	96 %		

**Single packaging**




Width 665 mm  
Height 84 mm  
Length 290 mm  
Weight 4,6 kg

**Bulk packaging**



Number of pieces/tape in meters pack 1 szt.  
zb  
Width 7110 mm  
Height of collective packaging 1160 mm  
Length 3360 mm  
Weight  
Volume 27,71 m<sup>3</sup>

**Europallet**



Quantity collective euro pallet 48  
Weight of a euro pallet 284,2 kg  
Pallet height 192 cm  
Number of layers 1