


code: 245640 EAN: 5901583245640

LED line® UFO T-Series 100-277V 150W 22500LM 4000K 120°DIM





High luminous efficacy ensured by high quality CREE branded LEDs.

This product is equipepd with a MEANWELL branded driver

which ensures reliable and fault-free operation even during



Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.



flicker free*

<u>~</u>}

120 °



Beam angle



Ambient temperature suitable for operation



Lifespan

Dimmable

| Parameter | Value |
|---------------------------------------|-------------|
| Luminous efficacy | 150 lm/W |
| Power | 150 W |
| Colour of the light | White |
| Energy efficiency class 2019/2015 | D |
| Luminous flux | 22500 lm |
| Correlated colour temperature | 4000 K |
| Colour consistency in McAdam ellipses | ≤6 |
| IP protection rating | 65 |
| Warranty (years) | 5 |
| Dimmable function | 1-10 |
| Survival factor | 0.9 |
| Lifetime L70B50 | 50 000 |
| Supply voltage range and voltage type | 100-277 VAC |
| Frequency of the supply voltage | 50/60Hz |
| | |

Wygenerowano 05-02-2025 godz 13:02 z systemu PIM B2B - LED Line



Manufacturer issues a 5-year warranty for this product.



voltage

00-277 VA

SMD3030

216

The power supply system used allows for smooth adjustment of light intensity using an appropriate dimmer.

Voltage range and voltage type

LED type

LED quantity

| Parameter | Value |
|--|-----------|
| Material (housing) | aluminum |
| LED type | SMD3030 |
| LED quantity | 216 |
| Not dimmable | ТАК |
| Compatible dimmer type | 1-10V |
| Lifespan | 50000 |
| Power Factor | 0,95 |
| Number of on/off cycles | 50000 |
| Colour consistency in McAdam ellipses | ≤6 |
| Ambient temperature suitable for operation | -40÷45 °C |
| For indoor and outdoor use | YES |
| IEC protection class | 1 |
| IK protection rating | 08 |
| Full box quantity | 1 pc |
| | |



| Colour rendering index Ra | 70 |
|------------------------------|---------------|
| Colour | black |
| The lumen maintenance factor | 96 % |
| Lamp's diameter | 260 |
| Beam angle | 120 ° |
| Material (cover) | polycarbonate |

| Lamp's warm-up time to 60% | 1 |
|-------------------------------|--------|
| Height | 250 mm |
| Product weight with packaging | 4150 g |
| Master carton weight (kg) | 41,5 |
| Energy class | A+ |
| | |

Luminous [cd/klm]

C0 - C180[°]**C90 - C270**

330 mm


330 mm

4,66 kg

0,023 m3

215


Single packaging



Width Height Length Weight

330 mm 215 mm 330 mm 4,66 kg 1

Bulk packaging



Width Length Weight Volume Europallet



Weight of a euro pallet