

LED line

Code: 245640

EAN: 5901583245640

**Highbay luminaire UFO T 4000K 150W
22500lm 120° IP65 black LITE 1-10V**



The LED line UFO T 150W 4000K is a perfect solution for demanding users. It offers a light output of 150 lm/W and a total light stream of as much as 22500 lm, providing clear and even lighting. High quality materials such as durable aluminum and polycarbonate tin guarantee resistance to atmospheric conditions.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5
Power	• 150 W
Voltage	• 100-277 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	70
IK protection rating	08
IEC protection class	I
Luminous efficacy	150
Luminous flux	22500
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
L80B* – difference B10–B50 ≈ 1% (according to LightingEurope) – negligible	35000 h
Survival factor	0.9
Dimmable function	1-10

Parameter	Value
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	120
LED type	SMD3030
LED quantity	216
Compatible dimmer type	1-10V
Lifespan	50 000 h
Power Factor	0,95
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-40÷45
Height	250
Fixture's diameter	260 mm
Colour	black
Material (housing)	Aluminium
Material (cover)	Polycarbonate

LED line


Code: 245640

EAN: 5901583245640

**Highbay luminaire UFO T 4000K 150W
22500lm 120° IP65 black LITE 1-10V**




Technical drawing

Light distribution



Additional product photos

Logistics data



Single packaging

Quantity	1
Width	330 mm
Height	215 mm
Length	330 mm
Weight	4,66 kg

Bulk packaging

Quantity	1
Width	330 mm
Height	215 mm
Length	330 mm
Volume	0,023 m3
Weight	41,5 kg
Comments	

Europallet

Quantity	42
Height	1649 mm
Quantity in layer	6
Number of layers	7
Bulk quantity	42
Weight	195,72 kg

LED line

Code: 245640

EAN: 5901583245640

**Highbay luminaire UFO T 4000K 150W
22500lm 120° IP65 black LITE 1-10V**

Example application