

LED line PRIME

Code: 204539-AW3HAT

EAN: 5905378216655

Panel Backlit 34W CCT 4760lm UGR<19
62x62 emergency module 3h autotest
PRIME



The LED backlit panel 34W CCT from LED line PRIME provides excellent light efficiency of 4760 lm. With an UGR ratio of <19, it is ideal for places requiring visual comfort. Thanks to the possibility of operating in emergency mode up to 3 hours and self-test function, it guarantees reliability in critical situations. Energy class C and life exceeding 50,000 hours emphasize its efficiency.



Technical data

Parameter	Value	Parameter	Value
Operating time in emergency mode	3 h	The lumen maintenance factor	96
Emergency module test	autotest	Beam angle	90
Voltage	<ul style="list-style-type: none">220-240 V AC	Material (cover)	polystyrene
Luminous efficacy	140	Material (housing)	Aluminium
Colour of the light	White	LED type	SMD LED 2835
Energy efficiency class 2019/2015	C	LED quantity	128
Luminous flux	4760	Power Factor	0,9
Colour consistency in McAdam ellipses	≤6	Number of on/off cycles	50000
Warranty (years)	5	Colour consistency in McAdam ellipses	≤6
IP protection rating	IP20	Ambient temperature suitable for operation	-20÷40
Dimmable function	Triac	For indoor use	Inside
Survival factor	0.9	IEC protection class	II
Lifetime L70B50	50 000 h	IK protection rating	02
Frequency of the supply voltage	50/60Hz	Lamp's warm-up time to 60%	1 s
Colour rendering index Ra	80	Correlated colour temperature	<ul style="list-style-type: none">3000 K4000 K5000 K
Colour	White	Power	<ul style="list-style-type: none">34 W

LED line PRIME

Code: 204539-AW3HAT



EAN: 5905378216655

**Panel Backlit 34W CCT 4760lm UGR<19
62x62 emergency module 3h autotest
PRIME**


Technical drawing

Light distribution


Additional product photos




Logistics data



Single packaging



Bulk packaging



Europallet

LED line PRIME

Code: 204539-AW3HAT

EAN: 5905378216655

**Panel Backlit 34W CCT 4760lm UGR<19
62x62 emergency module 3h autotest
PRIME**

Example application