

LED line PRIME


Code: 476029

EAN: 5907777476029

Linear luminaire FUSION 4000K 60W
7800lm LR40° IP20 150cm black PRIME



FUSION 60W 4000K linear mounting from LED line PRIME is a modern lighting solution that delivers 130 lm/W efficiency and a total light stream of 7800 lm. The product is characterized by IP20 leak class and IK08 impact resistance, making it suitable for internal applications. Thanks to the adjustable LR40° lens, it allows precise light transmission.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	C
Warranty	5/7*
Power	• 60 W
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	08
IEC protection class	I
Luminous efficacy	130
Luminous flux	7800
The lumen maintenance factor	96
Lifetime L70B50	50 000 h

Parameter	Value
L80B* – difference B10–B50 ≈ 1% (according to LightingEurope) – negligible	35000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
Sling length	200 cm
Standby power	0
Mounting type	mixed
Frequency of the supply voltage	50/60Hz
Power Factor	0,9
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷45
For indoor use	Inside
Height	52


LED line PRIME

Code: 476029


EAN: 5907777476029

Linear luminaire FUSION 4000K 60W
7800lm LR40° IP20 150cm black PRIME

Technical drawing



Light distribution



Additional product photos




Logistics data




Single packaging

Width	1444 mm
Height	52 mm
Length	70 mm
Weight	1,97 kg



Bulk packaging

Quantity	12
Width	1550 mm
Height	260 mm
Length	260 mm
Volume	0,104 m3
Weight	23,89 kg
Comments	



Europallet

Quantity	144
Height	1550 mm
Quantity in layer	144
Number of layers	1
Bulk quantity	144
Weight	286,8 kg

LED line PRIME

Code: 476029

EAN: 5907777476029

**Linear luminaire FUSION 4000K 60W
7800lm LR40° IP20 150cm black PRIME**

Example application