

LED line LITE

Code: 246791

EAN: 5901583246791

**DOWNLIGHT EASY FIX 2700K 12W
850lm square IP20 16.5x16.5cm White
LITE**



The LED Easy Fix panel with 12W power, providing a light stream of 850 lumens, provides a pleasant warm light with a colour temperature of 2700 K. Its innovative design and dimensions 163 x 163 x 14 mm allow easy installation, perfectly fitting into a variety of interior arrangements. High E-class energy efficiency and Ra colour reproduction factor at level 80 guarantee excellent light quality.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	3
Power	• 12 W
Voltage	• 220-260 V AC
Correlated colour temperature	• 2700 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IEC protection class	II
Luminous efficacy	71
Luminous flux	850
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6

Parameter	Value
Frequency of the supply voltage	50/60Hz
Beam angle	120
LGP	GLASS
LED type	SMD2835
LED quantity	56
Power Factor	0,5
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-5+40
For indoor use	Inside
Mounting hole diameter	60-135
Height	14
Colour	white
Material (housing)	Polyamide
Material (cover)	Polystyrene


LED line LITE

Code: 246791


EAN: 5901583246791

**DOWNLIGHT EASY FIX 2700K 12W
850lm square IP20 16.5x16.5cm White
LITE**

Technical drawing






Light distribution



Additional product photos

Logistics data



Single packaging

Quantity	1
Width	163 mm
Height	14 mm
Length	163 mm
Weight	0,39 kg

Bulk packaging

Quantity	40
Width	380 mm
Height	360 mm
Length	430 mm
Volume	0,058 m3
Weight	20 kg
Comments	

Europallet

Quantity	720
Height	1800 mm
Quantity in layer	160
Number of layers	5
Bulk quantity	800
Weight	318 kg

LED line LITE

Code: 246791

EAN: 5901583246791

**DOWNLIGHT EASY FIX 2700K 12W
850lm square IP20 16.5x16.5cm White
LITE**

Example application