

LED line PRIME

Code: 204263

EAN: 5905378204263

LED line PRIME FUSION linear lamp
60W 4000K 7800lm LR40° white



FUSION 60W linear setting from the LED line PRIME is a perfect solution for modern spaces. It is characterized by a light stream of 7800 lumens and a colour temperature of 4000 K, which provides ideal light conditions. 130 lm/W efficiency guarantees energy savings. The solid aluminium body protects against overheating, which promises long product life. The frame meets IP20 and IK08 standards.



Technical data

Parameter	Value
Voltage	• 220-240 V AC
Sling length	200 cm
Luminous efficacy	130
Colour of the light	White
Energy efficiency class 2019/2015	C
Luminous flux	7800
Colour consistency in McAdam ellipses	≤6
Standby power	0
Warranty (years)	5
IP protection rating	IP20
Survival factor	0.9
Lifetime L70B50	50 000 h

Parameter	Value
Mounting type	mixed
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
The lumen maintenance factor	96
Power Factor	0,9
Ambient temperature suitable for operation	-20÷45
For indoor use	Inside
IEC protection class	I
IK protection rating	08
Lamp's warm-up time to 60%	1 s
Correlated colour temperature	• 4000 K
Power	• 60 W

LED line PRIME

Code: 204263


EAN: 5905378204263

**LED line PRIME FUSION linear lamp
60W 4000K 7800lm LR40° white**


Technical drawing

Light distribution


Additional product photos




Logistics data



Single packaging



Bulk packaging



Europallet

LED line PRIME

Code: 204263

EAN: 5905378204263

**LED line PRIME FUSION linear lamp
60W 4000K 7800lm LR40° white**

Example application