

LED line PRIME


Code: 477415

EAN: 5907777477415

LED line® downlight 30W 3000lm 4000K QUANTUM



LED line downlight 30W 3000lm 4000K QUANTUM is an innovative lighting setting from the LED line PRIME, providing high light performance of 3000 lm at 30 W. Neutral colour of light 4000 K favours visual comfort and realistic color reproduction ($R_a \geq 85$). The construction made of aluminium and polycarbonate guarantees durability and aesthetics.



Technical data

Parameter	Value
Voltage	• 220-240 V AC
Luminous efficacy	100
Colour of the light	White
Energy efficiency class 2019/2015	F
Luminous flux	3000
Colour consistency in McAdam ellipses	≤ 3
Warranty (years)	5
IP protection rating	IP20
Survival factor	0.9
Lifetime L70B50	50 000 h
Wire length	150 mm
Output current	0,75
Colour rendering index Ra	85
Colour	White
The lumen maintenance factor	96
Fixture's diameter	170 mm
Beam angle	60
Material (cover)	polycarbonate

Parameter	Value
Material (housing)	Aluminium
LED type	COB
LED quantity	1
Lifespan	50 000 h
Power Factor	0,9
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤ 3
Ambient temperature suitable for operation	-5÷40
Installation method	recessed
Mounting hole diameter	155
For indoor use	Inside
IEC protection class	II
IK protection rating	03
Lamp's warm-up time to 60%	1 s
Energy class	A+ / F
Correlated colour temperature	• 4000 K
Power	• 30 W


LED line PRIME

Code: 477415


EAN: 5907777477415

**LED line® downlight 30W 3000lm
4000K QUANTUM**

Technical drawing




Light distribution




Additional product photos




Logistics data



Single packaging



Bulk packaging



Europallet

LED line PRIME

Code: 477415

EAN: 5907777477415

**LED line® downlight 30W 3000lm
4000K QUANTUM**

Example application