

LED line PRIME

Code: 478481-SKY

EAN: 5905378218420

LED line® Panel 2in1 30W 4000K 3600lm square



The 30W Skyframe PRIME 2in1 LED panel is a modern lighting solution that emits white light with a colour temperature of 4000K and a light stream of 3600 lm. It is characterized by a wide light angle of 120°. Made of high quality materials, including aluminum and polycarbonate, ensures durability and aesthetics. Thanks to the possibility of plastering and letting in, it fits perfectly into a variety of interiors.



Technical data

Parameter	Value
Voltage	• 220-240 V AC
Luminous efficacy	120
Colour of the light	White
Energy efficiency class 2019/2015	E
Luminous flux	3600
Colour consistency in McAdam ellipses	≤6
Warranty (years)	5
IP protection rating	IP20
Survival factor	0.9
Lifetime L70B50	50 000 h
Working current	0,1449
Dimmable	NO
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	White
The lumen maintenance factor	96
Beam angle	120
LGP	PMMA

Parameter	Value
Material (cover)	polycarbonate
Material (housing)	Aluminium
LED type	JUFEI 4014
LED quantity	196
Lifespan	50 000 h
Power Factor	0,9
Number of on/off cycles	20000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷45
Installation method	2in1 recessed and surface
For indoor use	Inside
IEC protection class	II
IK protection rating	02
Lamp's warm-up time to 60%	1 s
Energy class	A++
Correlated colour temperature	• 4000 K
Power	• 30 W

LED line PRIME


Code: 478481-SKY

EAN: 5905378218420



**LED line® Panel 2in1 30W 4000K
3600lm square**

Technical drawing


Light distribution




Additional product photos




Logistics data



Single packaging



Bulk packaging



Europallet

LED line PRIME

Code: 478481-SKY

EAN: 5905378218420

**LED line® Panel 2in1 30W 4000K
3600lm square**

Example application