

LED line LITE

Code: 202306

EAN: 5905378202306

**LED bulb E14 2700K 5W 600lm 230V
360° FILAMENT C35 DIM Glass LITE**



LED bulb E14 5W 2700K 600lm FILAMENT C35 DIM from LED line LITE is an ideal combination of aesthetics and energy efficiency. It is characterized by a light stream of 600 lumens and a performance of 120 lm/W, which provides excellent energy savings. IP20 leak class guarantees reliability in dry interiors.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	3
Power	• 5 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 2700 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
Luminous efficacy	120
Luminous flux	600 lm
The lumen maintenance factor	96
Lifetime L70B50	25 000 h
Survival factor	0.9
Dimmable function	Triac
Colour consistency in McAdam ellipses	≤6

Parameter	Value
Frequency of the supply voltage	50/60Hz
Lamp's type	C35
Beam angle	360 °
LED type	Filament
LED quantity	4
Lifespan	25 000 h
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	98
Fixture's diameter	35 mm
Material	Glass
Material (housing)	Glass
Material (cover)	glass


LED line LITE

Code: 202306

EAN: 5905378202306

**LED bulb E14 2700K 5W 600lm 230V
360° FILAMENT C35 DIM Glass LITE**

Technical drawing






Light distribution

Additional product photos



Logistics data



Single packaging

Quantity	1
Width	60 mm
Height	115 mm
Length	60 mm
Weight	0,02 kg

Bulk packaging

Quantity	100
Width	610 mm
Height	235 mm
Length	150 mm
Volume	0,021 m3
Weight	2,53 kg

Europallet

Height	1880 mm
Quantity in layer	800
Number of layers	8
Bulk quantity	6400
Weight	161,92 kg

LED line LITE

Code: 202306

EAN: 5905378202306

**LED bulb E14 2700K 5W 600lm 230V
360° FILAMENT C35 DIM Glass LITE**

Example application

