

LED line LITE

Code: 241147

EAN: 5901583241147

LED line® strip 300 SMD 24V 11000K
4,8W IP65



product_card.label_technical_data

Parameter	Value
Luminous efficacy	83 lm/W
Colour of the light	White
Energy efficiency class 2019/2015	G
Colour consistency in McAdam ellipses	≤6
Warranty (years)	3
Dimmable function	PWM
Survival factor	0.9
Minimum purchase quantity	5
Lifetime L70B50	50 000
Wattage (lm)	4,8 W
Luminous flux (lm)	400lm
Current (lm)	0,2
Colour rendering index Ra	80
Metres per roll	5
The lumen maintenance factor	96 %
Beam angle	120 °
LED type	SMD3528
Not dimmable	TAK
Compatible dimmer type	PWM

Parameter	Value
Laminate (colour)	White
Laminate (thickness)	2
LED quantity (lm)	60
Cutting section	10
Type of adhesive tape	3M 300 LSE
Lifespan	100000
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷45 °C
For indoor and outdoor use	YES
IEC protection class	III
Full box quantity	75 pc
Lamp's warm-up time to 60%	1
Width	8 mm
Height	3 mm
Energy class	A+
Power	• 4.8
Voltage	• 24 V DC
Correlated colour temperature	• 11000 K


LED line LITE

Code: 241147


EAN: 5901583241147

LED line® strip 300 SMD 24V 11000K
4,8W IP65

product_card.label_dimensions




product_card.label_curve_light




product_card.label_product_gallery

product_card.label_logistic_data




Single packaging

Width	180 mm
Height	20 mm
Length	180 mm
Weight	0,2 kg



Bulk packaging

Number of pieces/tape in meters pack zb	40 szt.
Width	360 mm
Height of collective packaging	180 mm
Length	320 mm
Weight	7,66 kg
Volume	0,020 m3



Europallet

Number of pieces/tapes in meters euro pallet	12000 m
Quantity collective euro pallet	2400 szt.
Weight of a euro pallet	484,6 kg
Pallet height	1800 mm
Quantity in 1 layer	240 szt.
Number of layers	10

LED line LITE

Code: 241147

EAN: 5901583241147

**LED line® strip 300 SMD 24V 11000K
4,8W IP65**

Example application