




code: 248733    EAN: 5901583248733

**LED line® UFO T-Series 220-240V 200W**  
**26000LM 4000K 90°**



This product has been contrued with the use of high quality LIFUD branded driver.



High luminous efficacy is ensured by the use of high quality LUMILEDS branded LEDs.



FLICKER FREE™ system guarantees no harmful flickering effect and ensures safety for users' eyesight.



Voltage range and voltage type



Motion detection angle



Lifespan



Dimmable



Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.



Manufacturer issues a 5-year warranty for this product.



Beam angle



Ambient temperature suitable for operation




LED type




LED quantity

Parameter	Value
Luminous efficacy	130 lm/W
Power	200 W
Colour of the light	White
Energy efficiency class 2019/2015	D
Luminous flux	26000 lm
Correlated colour temperature	4000 K
Colour consistency in McAdam ellipses	≤6
IP protection rating	65
Warranty (years)	5
Survival factor	0.9
Lifetime L70B50	50 000
Supply voltage range and voltage type	220-240 VAC
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	black
The lumen maintenance factor	96 %
Lamp's diameter	320
Beam angle	90 °

Parameter	Value
Material (cover)	polycarbonate
Material (housing)	aluminum
LED type	SMD3030
LED quantity	324
Lifespan	50000
Power Factor	0,95
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-40÷45 °C
For indoor and outdoor use	YES
IEC protection class	I
Full box quantity	1 pc
Lamp's warm-up time to 60%	1
Height	250 mm
Product weight with packaging	5400 g
Master carton weight (kg)	54
Energy class	A+




Single packaging




Width	390 mm
Height	215 mm
Length	390 mm
Weight	5,77 kg
	1

Bulk packaging



Width	1
	390 mm
	215
Length	390 mm
Weight	5,77 kg
Volume	0,032 m3

Europallet



Weight of a euro pallet	42
	242,34 kg
	1649
	6
	7