

LED line PRIME

Code: 201934

EAN: 5905378201934

LED line PRIME LED MR16 8,5W 2700K
1020lm 10-18V AC/DC



product_card.label_technical_data

Parameter	Value	Parameter	Value
Luminous efficacy	120 lm/W	Beam angle	120 °
Colour of the light	White	Material (housing)	Ceramic
Energy efficiency class 2019/2015	E	LED type	SMD2835
Luminous flux	1020 lm	Lifespan	30000
Colour consistency in McAdam ellipses	≤6	Power Factor	0,5
IP protection rating	IP20	Number of on/off cycles	50000
Warranty (years)	5	Colour consistency in McAdam ellipses	≤6
Survival factor	0.9	Ambient temperature suitable for operation	-5+40 °C
Lifetime L70B50	30 000	For indoor use	Inside
Material	Ceramic	Full box quantity	100 pc
Frequency of the supply voltage	50/60Hz	Lamp's warm-up time to 60%	1
Colour rendering index Ra	80	Height	50 mm
Colour	White	Power	• 8.5 W
The lumen maintenance factor	96 %	Voltage	• 10-18 V AC/DC
Lamp's type	MR16	Correlated colour temperature	• 2700 K
Lamp's diameter	50		

LED line PRIME

Code: 201934

EAN: 5905378201934

LED line PRIME LED MR16 8,5W 2700K
1020lm 10-18V AC/DC


product_card.label_dimensions

product_card.label_curve_light

product_card.label_product_gallery




product_card.label_logistic_data




Single packaging

Width	20 mm
Height	20 mm mm
Length	76 mm mm
Weight	0,06 kg kg
	1



Bulk packaging

Number of pieces/tape in meters pack zb	100 szt.
Width	575 mm mm
Height of collective packaging	145 mm
Length	280 mm mm
Weight	7 kg kg
Volume	0,023 m3 m3



Europallet

Quantity collective euro pallet	5200 szt.
Weight of a euro pallet	364 kg
Pallet height	1885 mm
Quantity in 1 layer	400 szt.
Number of layers	13

LED line PRIME

Code: 201934

EAN: 5905378201934

**LED line PRIME LED MR16 8,5W 2700K
1020lm 10-18V AC/DC**

Example application