


LED line® strip 600 SMD 12V red 9,6W IP65



Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.



This product is featured by a high degree of IP protection, which makes it suitable for a broader range of lighting applications and offers high safety of use.



Beam angle



Ambient temperature suitable for operation



LED quantity (1m)



Yellow free technology means that the housing of this product is made of high quality material which is resistant to yellowing degeneration caused by UV radiation, thanks to which the product maintains its aesthetic appearance for many years.



Manufacturer issues a 3-year warranty for this product.



Voltage range and voltage type



LED type




Dimmable

Parameter	Value
Colour of the light	Red
Warranty (years)	3
Dimmable function	PWM
Minimum purchase quantity	5
Wattage (1m)	9,6 W
Current (1m)	0,8
Supply voltage range and voltage type	12 VDC
Metres per roll	5
The lumen maintenance factor	>0,7 %
Beam angle	120 °
LED type	SMD3528
Not dimmable	TAK
Compatible dimmer type	PWM
Laminate (colour)	White
Laminate (thickness)	2


Parameter	Value
LED quantity (1m)	120
Cutting section	2,5
Type of adhesive tape	3M 300 LSE
Lifespan	100000
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤3
Ambient temperature suitable for operation	-20÷45 °C
For indoor and outdoor use	YES
IEC protection class	III
Full box quantity	75 pc
Lamp's warm-up time to 60%	1
Width	8 mm
Height	3 mm
Product weight with packaging	205 g
Master carton weight (kg)	15,38

Single packaging




1

Bulk packaging



Width 100
340 mm
280
Length 440 mm
Weight 0,16 kg
Volume 0,042 m³

Europallet



Weight of a euro pallet 24
3,84 kg
984
8
3