

LED line LITE

Code: 217522

EAN: 5905378217522

**Hermetic luminaire LINERIS 6500K 36W  
4320lm IP65 120cm gray 3x1,5mm LITE**



The hermetic fixture LINERIS 36W 4320lm 6500K IP65 from the renowned brand LED line LITE is an excellent solution in the field of lighting. It features high luminous efficiency at the level of 120 lm/W and a luminous flux of as much as 4320 lumens.

Thanks to the IP65 protection class, the product is resistant to water and contaminants, ensuring long-lasting use.



**Technical data**

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	3
Power	• 36 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 6500 K
Colour of the light	White
IK protection rating	08
IEC protection class	I
Luminous efficacy	120
Luminous flux	4320
The lumen maintenance factor	96
Lifetime L70B50	27 000 h

Parameter	Value
Survival factor	0,9
Mounting type	mixed
Frequency of the supply voltage	50/60Hz
CRI colour rendering index	80
Beam angle	120
Power Factor	0,9
Number of on/off cycles	18000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
Height	60
Material (housing)	Polycarbonate
Material (cover)	Polycarbonate


LED line LITE

Code: 217522


EAN: 5905378217522

**Hermetic luminaire LINERIS 6500K 36W  
4320lm IP65 120cm gray 3x1,5mm LITE**

**Technical drawing**



**Light distribution**



**Additional product photos**



**Logistics data**



**Single packaging**

Quantity	1
Width	70 mm
Height	67 mm
Length	1255 mm
Weight	1,109 kg

**Bulk packaging**

Quantity	12
Width	300 mm
Height	230 mm
Length	1250 mm
Weight	12,8 kg

**Europallet**

Quantity	144
Quantity in layer	12
Number of layers	1
Bulk quantity	12
Weight	180 kg

---

LED line LITE

Code: 217522

EAN: 5905378217522

**Hermetic luminaire LINERIS 6500K 36W  
4320lm IP65 120cm gray 3x1,5mm LITE**

---

**Example application**