


LED line® UFO T-Series 220-240V 200W 26000LM 4000K 120°



LED provided by
LUMILEDS

High luminous efficacy is ensured by the use of high quality LUMILEDS branded LEDs.



This product has been contrued with the use of high quality LIFUD branded driver.



Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.



Beam angle



LED type



Manufacturer issues a 5-year warranty for this product.



FLICKER FREE™ system guarantees no harmful flickering effect and ensures safety for users' eyesight.



Voltage range and voltage type



Ambient temperature suitable for operation



Lifespan




LED quantity

Parameter	Value
Luminous efficacy	130 lm/W
Power	200 W
Colour of the light	White
Energy efficiency class 2019/2015	E
Luminous flux	26000 lm
Correlated colour temperature	4000 K
Colour consistency in McAdam ellipses	≤6
IP protection rating	65
Warranty (years)	5
Dimmable function	No
Survival factor	0.9
Lifetime L70B50	50 000
Supply voltage range and voltage type	220-240 AC
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	black
The lumen maintenance factor	96
Lamp's diameter	320
Beam angle	120 °
Material (cover)	polycarbonate


Parameter	Value
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-40 ÷ 45 °C
For indoor and outdoor use	YES
IEC protection class	I
IK protection rating	08
Full box quantity	1 pc
Lamp's warm-up time to 60%	1
Height	250 mm
Product weight with packaging (g)	5400 g
Master carton weight (kg)	54
EPREL ID	632 057
Date of first placement on the market	2017-01-01 00:48:26
Energy class	A+
Angle for useful luminous flux (EPREL)	Wide cone of 120 degrees
Is the product equipped with an integrated light source? (EPREL)	No
Non-directional or directional light source (EPREL)	DLS
Is this product a light source? (EPREL)	Yes
Mains or non- mains light source (EPREL)	MLS
Connected light source (EPREL)	No

Material (housing)	aluminum	Colour-tuneable light source (EPREL)	No
LED type	SMD3030	R9 colour rendering index value (EPREL)	14
LED quantity	324	Total luminous flux (EPREL)	26 000
Lifespan	50000	On-mode power P_{on} (EPREL)	200
Power Factor	0,95	Useful luminous flux Φ_{use} (EPREL)	22 400
Number of on/off cycles	50000	Beam angle in degrees (EPREL)	120

Luminous [cd/klm]




Single packaging




390
215
390
5,77
1

Bulk packaging



1

Europallet



6