

LED line PRIME

Code: 204010

EAN: 5905378204010

**Linear luminaire FUSION 4000K 20W
2600lm 120*120° IP20 60cm white
PRIME**



The 20W and 4000K FUSION linear luminaire emits 2600 lm of light is distinguished by modern design and high energy efficiency of 130 lm/W. The angle of light transmission is 120°, which provides even illumination of the space. Thanks to the use of durable aluminum, the housing is characterized by excellent heat draining and long-lasting life up to 50,000 h.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	C
Warranty	5/7*
Power	• 20 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	08
IEC protection class	I
Luminous efficacy	130
Luminous flux	2600
The lumen maintenance factor	96

Parameter	Value
Lifetime L70B50	50 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
Sling length	200 cm
Standby power	0
Mounting type	mixed
Frequency of the supply voltage	50/60Hz
Power Factor	0.9
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷45
For indoor use	Inside
Height	52

LED line PRIME

Code: 204010

EAN: 5905378204010


**Linear luminaire FUSION 4000K 20W
2600lm 120*120° IP20 60cm white
PRIME**

Technical drawing






Light distribution

Additional product photos



Logistics data



Single packaging

Width	586 mm
Height	52 mm
Length	70 mm
Weight	1,14 kg

Bulk packaging

Quantity	12
Width	690 mm
Height	260 mm
Length	260 mm
Volume	0,046 m3
Weight	13,93 kg
Comments	

Europallet

Quantity	288
Height	1710 mm
Quantity in layer	48
Number of layers	6
Bulk quantity	288
Weight	672 kg

LED line PRIME

Code: 204010

EAN: 5905378204010

**Linear luminaire FUSION 4000K 20W
2600lm 120*120° IP20 60cm white
PRIME**

Example application