

LED line LITE

Code: 200890

EAN: 5905378200890

DOWNLIGHT MOLLY 3000K 24W 2350lm square IP20 White LITE



LED line LITE Downlight MOLLY 24W produces an impressive 2350lm light stream. It is characterized by a pleasant warm light with a colour temperature of 3000K, which favors visual comfort. The use of SMD LEDs 2835 in combination with high Ra>80 colour reproduction rate provides a natural light effect. The product meets PN-EN standards, and IP20 seal class guarantees effectiveness in various interiors.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	3
Power	• 24 W
Voltage	• 170-260 V AC
Correlated colour temperature	• 3000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IEC protection class	II
Luminous efficacy	100
Luminous flux	2350
The lumen maintenance factor	96
Lifetime L70B50	30 000 h

Parameter	Value
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
LED type	SMD LED 2835
LED quantity	144
Power Factor	0.5
Number of on/off cycles	20000
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Mounting hole diameter	190-210
Height	26
Colour	White
Material (housing)	Polycarbonate


LED line LITE

Code: 200890


EAN: 5905378200890

**DOWNLIGHT MOLLY 3000K 24W 2350lm
square IP20 White LITE**

Technical drawing






Light distribution



Additional product photos



Logistics data



Single packaging

Quantity	1
Width	220 mm
Height	26 mm
Length	220 mm
Weight	0,373 kg

Bulk packaging

Quantity	40
Width	390 mm
Height	472 mm
Length	472 mm
Volume	0,015 m3
Weight	15,15 kg

Europallet

Quantity	640
Height	1,9 m
Quantity in layer	160
Number of layers	4
Bulk quantity	16
Weight	273 kg

LED line LITE

Code: 200890

EAN: 5905378200890

**DOWNLIGHT MOLLY 3000K 24W 2350lm
square IP20 White LITE**

Example application

