

LED line PRIME

Code: 205819-DALI

EAN: 5905378220058

Panel Backlit 34W 4000K 4760lm 60x60  
DALI PRIME



Backlit panel 34W 4000K 4760lm 60x60 PRIME is a modern light source that provides excellent light performance at 140 lm/W. Thanks to the colour of the light 4000 K and Ra colour reproduction factor at level 80, it achieves a natural lighting effect. Offering a light stream of as many as 4,760 lumens, it fits perfectly into a variety of interiors.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	C
Warranty	5
Power	• 34 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	02
IEC protection class	II
Luminous efficacy	140
Luminous flux	4760
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
Survival factor	0.9

Parameter	Value
Dimmable function	Triac
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	90
LED type	SMD LED 2835
LED quantity	128
Power Factor	0,9
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Colour	White
Material (housing)	Aluminium
Material (cover)	Polystyrene

LED line PRIME

Code: 205819-DALI

EAN: 5905378220058

**Panel Backlit 34W 4000K 4760lm 60x60  
DALI PRIME**

Technical drawing

Light distribution

Additional product photos

Logistics data



Single packaging



Bulk packaging



Europallet

---

LED line PRIME

Code: 205819-DALI

EAN: 5905378220058

**Panel Backlit 34W 4000K 4760lm 60x60  
DALI PRIME**

---

**Example application**