

LED line LITE

Code: 210110

EAN: 5905378210110

**DOWNLIGHT EASY FLEX 3CCT(3K/4K/5K)
12/15/18W 1440lm square IP20 black
LITE**



Downlight EASY FLEX 18-21-24W CCT is a modern LED line LITE lighting luminaire, characterized by a luminous flux performance of 2110 lumens. It allows to choose colour temperature in the range 3000 K, 4000 K and 5000 K, which provides flexibility in space arrangement. IP20 seal class guarantees protection against solid bodies larger than 12 mm and the IK05 protection level provides impact resistance.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	3
Power	<ul style="list-style-type: none"> • 12 W • 15 W • 18 W
Voltage	<ul style="list-style-type: none"> • 220-240 V AC
Correlated colour temperature	<ul style="list-style-type: none"> • 3000 K • 4000 K • 5000 K
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	05
IEC protection class	II
Luminous efficacy	90
Luminous flux	1440
The lumen maintenance factor	96
Lifetime L70B50	30 000 h

Parameter	Value
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	120
LED type	SMD2835
LED quantity	168
Number of on/off cycles	15000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
Installation method	3in1 surface mounted, flush mounted, suspended
Mounting hole diameter	65-175
Height	17
Colour	White


LED line LITE

Code: 210110


EAN: 5905378210110

**DOWNLIGHT EASY FLEX 3CCT(3K/4K/5K)
12/15/18W 1440lm square IP20 black
LITE**

Technical drawing






Light distribution



Additional product photos



Logistics data



Single packaging

Width	225 mm
Height	58 mm
Length	225 mm
Weight	0,57 kg

Bulk packaging

Quantity	20
Width	280 mm
Height	335 mm
Length	570 mm
Weight	11,40 kg

Europallet

Bulk quantity	
---------------	--

LED line LITE

Code: 210110

EAN: 5905378210110

**DOWNLIGHT EASY FLEX 3CCT(3K/4K/5K)
12/15/18W 1440lm square IP20 black
LITE**

Example application