

LED line LITE

Code: 210110

EAN: 5905378210110

LED line LITE Downlight EASY FLEX 18-21-24W CCT 2110lm round white



Downlight EASY FLEX 18-21-24W CCT is a modern LED line LITE lighting luminaire, characterized by a luminous flux performance of 2110 lumens. It allows to choose colour temperature in the range 3000 K, 4000 K and 5000 K, which provides flexibility in space arrangement. IP20 seal class guarantees protection against solid bodies larger than 12 mm and the IK05 protection level provides impact resistance.



Technical data

| Parameter                         | Value  |
|-----------------------------------|--|
| Energy efficiency class 2019/2015 | E  |
| Warranty                          | 3  |
| Power                             | <ul style="list-style-type: none"><li>12 W</li><li>15 W</li><li>18 W</li></ul>       |
| Voltage                           | <ul style="list-style-type: none"><li>220-240 V AC</li></ul>                         |
| Correlated colour temperature     | <ul style="list-style-type: none"><li>3000 K</li><li>4000 K</li><li>5000 K</li></ul> |
| Colour rendering index Ra         | 80   |
| IP protection rating              | IP20   |
| IK protection rating              | 05   |
| IEC protection class              | II   |
| Luminous efficacy                 | 90   |
| Luminous flux                     | 1440   |
| The lumen maintenance factor      | 96   |

| Parameter                                  | Value  |
|--|--|
| Lifetime L70B50                            | 30 000 h                                       |
| Colour consistency in McAdam ellipses      | ≤6   |
| Frequency of the supply voltage            | 50/60Hz  |
| Beam angle                                 | 120  |
| LED type                                   | SMD2835  |
| LED quantity                               | 168  |
| Number of on/off cycles                    | 15000  |
| Lamp's warm-up time to 60%                 | 1  |
| Ambient temperature suitable for operation | -20÷40   |
| Installation method                        | 3in1 surface mounted, flush mounted, suspended |
| Mounting hole diameter                     | 65-240   |
| Colour                                     | White  |


LED line LITE

Code: 210110


EAN: 5905378210110

## LED line LITE Downlight EASY FLEX 18-21-24W CCT 2110lm round white

### Technical drawing




### Light distribution




### Additional product photos




### Logistics data



Single packaging



Bulk packaging



Europallet

---

LED line LITE

Code: 210110

EAN: 5905378210110

**LED line LITE Downlight EASY FLEX 18-  
21-24W CCT 2110lm round white**

---

**Example application**