

LED line PRIME

Code: 200265

EAN: 5905378200265

**FLOODLIGHT 4000K 30W 4200lm 30°  
IP66 PRIME**



The 30W and 4200 lm LED line PRIME is the ideal solution for demanding conditions. It is characterized by energy efficiency of 140 lm/W and IP66 leak class, providing reliability in difficult weather conditions. It allows precise light steering thanks to a distribution angle of 30°. Aluminium housing material and hardened glass guarantee high durability.



**Technical data**

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5/7*
Power	• 30 W
Voltage	• 100-277 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	70
IP protection rating	IP66
IK protection rating	08
IEC protection class	I
Luminous efficacy	140
Luminous flux	4200
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
L80B* – difference B10–B50 ≈ 1% (according to LightingEurope) – negligible	35000 h

Parameter	Value
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
Wire length	890 mm
Mounting type	surface
Frequency of the supply voltage	50/60Hz
Beam angle	30
LED type	SMD2835
LED quantity	96
Power Factor	0.9
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-40÷45
Height	43,5
Material (housing)	Aluminium
Material (cover)	Tempered glass


LED line PRIME

Code: 200265


EAN: 5905378200265

**FLOODLIGHT 4000K 30W 4200lm 30°  
IP66 PRIME**

**Technical drawing**






**Light distribution**



**Additional product photos**



**Logistics data**



**Single packaging**

Width	252 mm
Height	43,5 mm
Length	213 mm
Weight	1 kg

**Bulk packaging**

Quantity	10
Width	480 mm
Height	285 mm
Length	320 mm
Volume	0,043 m3
Weight	10,35 kg
Comments	

**Europallet**

Quantity	200
Height	1710 mm
Quantity in layer	40
Number of layers	6
Bulk quantity	240
Weight	248,4 kg

---

LED line PRIME

Code: 200265

EAN: 5905378200265

**FLOODLIGHT 4000K 30W 4200lm 30°  
IP66 PRIME**

---

**Example application**