

LED line PRIME LED bulb E14 7W 6500K 1000lm 170-250V C37 Candle



Manufacturer issues a 5-year warranty for this product.



FLICKER FREE™ system guarantees no harmful flickering effect and ensures safety for users' eyesight.



Beam angle



LED type



142 lm
W



The structural design of this product ensures effective heat dissipation.



Voltage range and voltage type



Lamp type



Lifespan

Parameter	Value
Luminous efficacy	142lm/W
Power	7 W
Colour of the light	White
Energy efficiency class 2019/2015	D
Luminous flux	1000 lm
Correlated colour temperature	6500 K
Colour consistency in McAdam ellipses	≤6
IP protection rating	20
Warranty (years)	5
Dimmable function	No
Survival factor	0.9
Lifetime L70B50	30 000
Supply voltage range and voltage type	170-250V AC
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	White
The lumen maintenance factor	96
Lamp's type	C37
Lamp's diameter	37
Beam angle	220 °

Parameter	Value
LED type	SMD2835
Lifespan	30000
Power Factor	0,5
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
For indoor use	Inside
Full box quantity	100 pc
Lamp's warm-up time to 60%	1
Height	111 mm
Master carton weight (kg)	7
Angle for useful luminous flux (EPREL)	Sphere 360 degrees
Is the product equipped with an integrated light source? (EPREL)	No
Non-directional or directional light source (EPREL)	NDLS
Is this product a light source? (EPREL)	Yes
Mains or non- mains light source (EPREL)	MLS
Connected light source (EPREL)	No
Colour-tuneable light source (EPREL)	No
Total luminous flux (EPREL)	1 000
On-mode power P _{on} (EPREL)	7
Useful luminous flux Φ _{use} (EPREL)	1 000


Material (cover)	glass
Material (housing)	Ceramic

Beam angle in degrees (EPREL)	220
-------------------------------	-----

Single packaging



Bulk packaging



Europallet

