

LED line LITE

Code: 248788

EAN: 5901583248788

**DOWNLIGHT EASY FIX 4000K 6W 470lm  
round IP20 FI11.5cm White LITE**



LED panel Easy Fix 6W 4000K 470lm round from LED line LITE is an elegant lighting characterized by neutral white light, providing a pleasant atmosphere in each interior. Its light output is 470 lumens at 6W, which translates into efficiency at 78 lm/W. The materials used, such as polyamide and high quality polystyrene, guarantee durability. High resistance to fibrillation (SVM: 0.



**Technical data**

Parameter	Value
Energy efficiency class 2019/2015	E
Warranty	3
Power	• 6 W
Voltage	• 220-260 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IEC protection class	II
Luminous efficacy	78
Luminous flux	470
The lumen maintenance factor	96
Lifetime L70B50	30 000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz

Parameter	Value
Beam angle	120
LGP	GLASS
LED type	SMD2835
LED quantity	28
Power Factor	0,5
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-5÷40
For indoor use	Inside
Mounting hole diameter	55-90
Height	13
Fixture's diameter	113 mm
Colour	white
Material (housing)	Polyamide
Material (cover)	Polystyrene


LED line LITE

Code: 248788


EAN: 5901583248788

**DOWNLIGHT EASY FIX 4000K 6W 470lm  
round IP20 FI11.5cm White LITE**

**Technical drawing**






**Light distribution**



**Additional product photos**



**Logistics data**



**Single packaging**

Quantity	1
Width	136 mm
Height	43 mm
Length	124 mm
Weight	0,21 kg

**Bulk packaging**

Quantity	60
Width	390 mm
Height	280 mm
Length	430 mm
Volume	0,046 m3
Weight	16,1 kg
Comments	

**Europallet**

Quantity	1440
Height	1950 mm
Quantity in layer	240
Number of layers	5
Bulk quantity	1200
Weight	322 kg

---

LED line LITE

Code: 248788

EAN: 5901583248788

**DOWNLIGHT EASY FIX 4000K 6W 470lm  
round IP20 FI11.5cm White LITE**

---

**Example application**